

23 April 20

Sally McKinnon
Senior Contaminated Land and Ground Water Scientist
Gisborne District Council
15 Fitzherbert Street
PO Box 747
Gisborne 4010

By e-mail: Sally.McKinnon@gdc.govt.nz

Dear Sally,

Re: Matawhero Logyard Cell 3 bore monitoring: Consent - DL-2018-108538-00

Please see below the results of the monitoring undertaken on 27/03/2020 as required by conditions 10 – 28 of consent DL-2018-108538-00.

All recorded parameters, except dissolved zinc at bore GW02, were below consent trigger limits.

Kind Regards,



Christine Oakey
Senior Environmental Management Consultant
4Sight Consulting Ltd



Matawhero Log Yard (Eastland Port) - E004

Monthly Bore Monitoring



Attn: Christine Oakey (christineo@4sight.co.nz)

Sample Date: 27/03/2020

Sampler: Dion Williams

DO Probe: MER 138

Daily Summary Sheet

Weather Conditions: Sunny

Tidal Flow: High tide.

	GW02	New Monitoring Bore
Bore Conditions:	Good	Good
Surrounds Conditions:	Good	Good
Purging Results:	4L then sampled	10L then sampled

Comments: Slow recovery on both bores, but ok.

Analysis Report

Customer: Eastland Port	Date Received: 27/03/2020 9:55 AM
Address: 1 Kaiti Beach Road	Date Completed: 14/04/2020 10:16 AM
Gisborne, 4010	
Attention: Christine Oakey	Purchase Order #:

Sample Type: Water

	Units	2020001980 Bore GW02	2020001981 New Monitoring Bore
		27/03/2020 8:45	27/03/2020 9:45
Test			
Analytica Laboratories Report		20-13237	20-13237
Conductivity @25°C	µS/cm	992	1010
Dissolved Oxygen Field Test*	g/m ³	1.3	0.93
pH - Water		7.0	6.9
Salinity	ppt	0.4	0.4
Static Water Level	m	2.59	3.21
Temperature	°C	17.1	16.5

Comments: These samples were also analysed by Analytica Laboratories. Please see attached report.

Test Standards:

Test	Methodology
Analytica Laboratories Report	
Conductivity @25°C	APHA 23rd Ed 2510 B
Dissolved Oxygen Field Test*	APHA 23rd Ed 4500 OG
pH - Water	APHA 23rd 4500-H+ B
Salinity	APHA 23rd Ed 2520 B
Static Water Level	*
Temperature	APHA 23rd ed 2550 B

Authorised By:

Brenda Overend
Technician
KTP Chemistry and Microbiology

Certified By:

Tom Needham
Technician
KTP Chemistry and Microbiology



Tests indicated as
not accredited are outside
the scope of the
laboratory's accreditation

Methods marked with a * are not IANZ accredited.

This report shall not be reproduced except in full, without written approval of the laboratory.
"Detailed activity" stating the start and completion dates and times of individual tests have not been recorded on this report. This information is available upon request.



Certificate of Analysis

Linnaeus Laboratory Limited
 4 Banks Street
 Gisborne 4010

Attention: Shanna Hickling
 Phone: 06 867 8512
 Email: shanna@linnaeus.co.nz

Lab Reference: 20-13237
 Submitted by: Linnaeus Laboratory Limited
 Date Received: 30/03/2020
 Testing Initiated: 30/03/2020
 Date Completed: 9/04/2020
 Order Number: 1322
 Reference: N/A

Sampling Site: Matawhero Log Yard (Eastland Port)

Report Comments

Samples were collected by yourselves (or your agent) and analysed as received at Analytica Laboratories. Samples were in acceptable condition unless otherwise noted on this report. Specific testing dates are available on request.

Total Petroleum Hydrocarbons - Water


Client Sample ID			2020001980 Bore GW02	2020001981 New Monitoring Bore
Date Sampled			27/03/2020	27/03/2020
Analyte	Unit	Reporting Limit	20-13237-1	20-13237-2
C7-C9	g/m ³	0.2	<0.2	<0.2
C10-C14	g/m ³	0.2	<0.2	<0.2
C15-C36	g/m ³	0.3	<0.3	<0.3
C7-C36 (Total)	g/m ³	0.5	<0.5	<0.5

Elements in Water (Soluble)

Client Sample ID			2020001980 Bore GW02	2020001981 New Monitoring Bore
Date Sampled			27/03/2020	27/03/2020
Analyte	Unit	Reporting Limit	20-13237-1	20-13237-2
Copper	g/m ³	0.0002	0.0025	0.00068
Lead	g/m ³	0.00005	<0.000050	<0.000050
Zinc	g/m ³	0.001	0.047	0.0016

Method Summary

TPH in Water	Solvent extraction, silica cleanup, followed by GC-FID analysis (C7-C36). MFE Petroleum Industry Guidelines. (In accordance with in-house procedure based on US EPA 8015).
Soluble Trace Elements	Samples were analysed as received by the laboratory using ICP-MS following a 0.45µm membrane filtration (except when field filtered). In house procedure based on US EPA 200.8.



Kimmy Ignacio, B.Sc.
Technician



Sharelle Frank, B.Sc. (Tech)
Technologist

